

PS2-600 HR-04H

Solar Submersible Pump System for 4" wells

System Overview

Head max. 140 m
Flow rate max. 0.72 m³/h

Technical Data

Controller PS2-600

- Controlling and monitoring
- Control inputs for dry running protection, remote control etc.
- Protected against reverse polarity, overload and overtemperature
- Integrated MPPT (Maximum Power Point Tracking)
- Battery operation: Integrated low voltage disconnect

Power max. 0.70 kW
Input voltage max. 150 V
Optimum Vmp** > 68 V
Motor current max. 13 A
Efficiency max. 98 %
Ambient temp. -40...50 °C
Enclosure class IP68

Motor ECDRIVE 600-HR

- Maintenance-free brushless DC motor
- Water filled
- Premium materials, stainless steel: AISI 304/316
- No electronics in the motor

Rated power 0.70 kW
Efficiency max. 92 %
Motor speed 900...3 300 rpm
Insulation class F
Enclosure class IP68
Submersion max. 150 m

Pump End PE HR-04H***

- Non-return valve
- Premium materials, stainless steel: AISI 304/316
- Helical rotor pump

Efficiency max. 68 %



Pump Unit PU600 HR-04H (Motor, Pump End)

Borehole diameter min. 4,0 in
Water temperature max. 50 °C

Standards



2006/42/EC, 2004/108/EC, 2006/95/EC

IEC/EN 61702:1995, IEC/EN 62253 Ed.1

The logos shown reflect the approvals that have been granted for this product family. Products are ordered and supplied with the approvals specific to the market requirements.

**Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

***Specify temperature range on order




PS2-600 HR-04H

Solar Submersible Pump System for 4" wells

Pump Chart

Vmp* > 68 V



Dimensions and Weights


Controller

H1 = 352 mm
 H2 = 333 mm
 W1 = 207 mm
 W2 = 170 mm
 W3 = 164 mm
 D1 = 124 mm



Pump Unit

A = 780 mm
 B = 185 mm
 C = 595 mm
 D = 96 mm
 S = 1.25 in



	Net weight
Controller	5.6 kg
Pump Unit	11 kg
Motor	7.0 kg
Pump End	4.2 kg

*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

