

# PSk3-7 C-SJ30-6

## Solar Submersible Pump System for 6" wells

### System Overview

Head	max. 50 m
Flow rate	max. 42 m³/h

### Technical Data

#### Controller PSk3-7

- High efficiency solar pump controller
- Integrated hybrid power functions to mix solar with grid / generator power
- Integrated MPPT (Maximum Power Point Tracking)
- Multiple analogue and digital sensor
- Simple configuration with LORENTZ Assitant App
- Onboard data logging and system monitoring with real-time and historic data views
- Inbuilt water applications to manage your pumping system
- SunSensor included for unique pump and motor protection
- Active temperature management

Power	max. 8,3 kW
Input voltage	max. 850 V
Optimum Vmp**	> 575 V
Motor current	max. 13 A
Efficiency	max. 98 %
Ambient temp.	-25...60 °C
Enclosure class	IP66

#### Motor AC DRIVE SUB 6" 5.5kW

- Highly efficient 3-phase AC motor
- Frequency: 25...51 Hz
- Premium materials, stainless steel: AISI 304
- No electronics in the motor

Efficiency	max. 85 %
Motor speed	1.400...2.905 rpm
Power factor	0,88
Insulation class	F
Enclosure class	IP68
Submersion	max. 150 m

#### Pump End PE C-SJ30-6

- Non-return valve
- Premium materials, stainless steel: AISI 304
- Centrifugal pump

Efficiency	max. 65 %
------------	-----------

#### Pump Unit PU7k C-SJ30-6 (Motor, Pump End)

Borehole diameter	min. 6,0 in
Water temperature	max. 30 °C****

### Standards



2006/42/EC, 2004/108/EC, 2006/95/EC

IEC/EN 61702:1995, IEC/EN 62253 Ed.1

The logos shown reflect the approvals that have been granted for this product family. Products are ordered and supplied with the approvals specific to the market requirements.

\*\*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

\*\*\*\*Special solutions available for >30 °C, please consult your distributor




## PSk3-7 C-SJ30-6

Solar Submersible Pump System for 6" wells

### Pump Chart


Vmp\* > 575 V



### Dimensions and Weights


#### Controller

- H = 428 mm
- H1 = 390 mm
- H2 = 270 mm
- W1 = 280 mm
- W2 = 250 mm
- D = 6,0 mm



#### Pump Unit

- A = 1.610 mm
- B = 750 mm
- C = 860 mm
- D = 143 mm
- E = 133 mm
- S = 3 in



	Net weight
Controller	
Pump Unit	64 kg
Motor	48 kg
Pump End	16 kg

\*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

